


SLIMLINE LANCE COUPLINGS

- Used to couple rigid and flex lances without the use of glands and collars to allow them to fit into tubes
- Additional couplings available upon request

PART NO.	CONNECTION 1	CONNECTION 2	MAX. WORKING PRESSURE	
			psi	bar
AF 073-MP4LMP4L-SL	1/4 MPLH Female	1/4 MPLH Female	22,000	1,500
AF 073-MP4RMP4L-SL	1/4 MPRH Female	1/4 MPLH Female	22,000	1,500
AF 073-MP4RMP4R-SL	1/4 MPRH Female	1/4 MPRH Female	22,000	1,500
AF 073-MP4RMP6R-SL	1/4 MPRH Female	3/8 MPRH Female	22,000	1,500
AF 073-MP6LMP6L-SL	3/8 MPLH Female	3/8 MPLH Female	22,000	1,500
AF 073-MP6RMP6L-SL	3/8 MPRH Female	3/8 MPLH Female	22,000	1,500
AF 073-MP6RMP6R-SL	3/8 MPRH Female	3/8 MPRH Female	22,000	1,500
AF 073-MP6LMP9L-SL	3/8 MPLH Female	9/16 MPLH Female	22,000	1,500
AF 073-MP6RMP9R-SL	3/8 MPRH Female	9/16 MPRH Female	22,000	1,500
AF 073-MP9LMP9L-SL	9/16 MPLH Female	9/16 MPLH Female	22,000	1,500
AF 073-MP9RMP9L-SL	9/16 MPRH Female	9/16 MPLH Female	22,000	1,500
AF 073-MP9RMP9R-SL	9/16 MPRH Female	9/16 MPRH Female	22,000	1,500
AF 073-MP9LMP12L-SL	9/16 MPLH Female	3/4 MPLH Female	22,000	1,500
AF 073-MP9RMP12R-SL	9/16 MPRH Female	3/4 MPRH Female	22,000	1,500
AF 073-MP12LMP12L-SL	3/4 MPLH Female	3/4 MPLH Female	22,000	1,500
AF 073-MP12RMP12L-SL	3/4 MPRH Female	3/4 MPLH Female	22,000	1,500
AF 073-MP12RMP12R-SL	3/4 MPRH Female	3/4 MPRH Female	22,000	1,500



FITTINGS

MANIFOLDS

- Manifolds used in 2L, 3L, BRLM systems

PART NO.	OUTLET CONNECTION	INLET CONNECTION	MAWP PSI/BAR	
			psi	bar
ABX 369-MP12	9/16 MP Female	3/4 MP Female	22,000	1,500

