

HOSE, FITTINGS & ACCESSORIES

StoneAge is your complete solution.
Hoses, Fittings, Tools, Accessories,
All in one location!

WATERBLAST ACCESSORIES

SAPPHIRE NOZZLES

For High Pressure Applications

These nozzles are used for high pressure jetting applications where water filtration of 10 micron or better is required. Jeweled orifices make the best quality, longest lasting jets possible, especially for ultra-high pressures.

- Pressure Range: 20–40k psi (1400–2800 bar)
- Flow Range: 0.2–4.8 gpm (0.75–18 l/min)



Shown larger than actual size.

SAFETY

ACCESSORIES TO HELP ENSURE JOB SITE SAFETY.

- Pneumatic Dumps
- Cartridges
- Diffusers
- Rupture Discs
- Pressure Gauges
- Pressure Relief Valves
- Whip Checks
- Safety Guards



LANCES/STINGERS

FOR PRESSURES UP TO 40K PSI/2800 BAR.



ADAPTERS/FITTINGS

A FULL RANGE OF PRODUCTS FOR APPLICATIONS UP TO 40K PSI/2800 BAR.

- Hose Connectors
- Gland Nuts & Collars
- Couplers
- Bushings



SUPPLY HOSES

A FULL RANGE OF PRODUCTS FOR APPLICATIONS UP TO 40K PSI/2800 BAR.



SAPPHIRE NOZZLE FLOW CHART (GPM)

ORIFICE I.D. in. mm	PRESSURE KPSI & (BAR)											AVAILABILITY		
	20 (1400)	22 (1500)	24 (1700)	26 (1800)	28 (1900)	30 (2100)	32 (2200)	34 (2300)	36 (2500)	38 (2600)	40 (2800)	OS4	OS6	OS7
.009 (0.23)	0.2	0.2	0.2	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3		•	
.010 (0.25)	0.3	0.3	0.3	0.3	0.3	0.3	0.4	0.4	0.4	0.4	0.4	•	•	
.011 (0.28)	0.3	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.5	0.5	0.5		•	•
.012 (0.30)	0.4	0.4	0.4	0.4	0.5	0.5	0.5	0.5	0.5	0.6	0.6	•	•	•
.013 (0.33)	0.5	0.5	0.5	0.5	0.6	0.6	0.6	0.6	0.6	0.6	0.7	•	•	•
.014 (0.36)	0.5	0.6	0.6	0.6	0.6	0.7	0.7	0.7	0.7	0.7	0.8	•	•	•
.015 (0.38)	0.6	0.7	0.7	0.7	0.7	0.8	0.9	0.8	0.8	0.9	0.9	•	•	•
.016 (0.41)	0.7	0.7	0.8	0.8	0.8	0.9	0.9	0.9	1.0	1.0	1.0	•	•	•
.017 (0.43)	0.8	0.8	0.9	0.9	0.9	1.0	1.0	1.0	1.1	1.1	1.1	•	•	•
.018 (0.46)	0.9	0.9	1.0	1.0	1.1	1.1	1.1	1.2	1.2	1.2	1.3	•	•	•
.019 (0.48)	1.0	1.0	1.1	1.1	1.1	1.2	1.3	1.3	1.3	1.4	1.4	•	•	•
.020 (0.51)	1.1	1.2	1.2	1.3	1.3	1.4	1.4	1.4	1.5	1.5	1.6	•	•	•
.021 (0.53)	1.2	1.3	1.3	1.4	1.4	1.5	1.5	1.6	1.6	1.7	1.7	•	•	•
.022 (0.56)	1.3	1.4	1.5	1.5	1.6	1.6	1.7	1.7	1.8	1.8	1.9	•	•	•
.023 (0.58)	1.5	1.5	1.6	1.7	1.7	1.7	1.8	1.9	1.9	2.0	2.0	•	•	•
.024 (0.61)	1.6	1.7	1.7	1.8	1.9	1.9	2.0	2.1	2.1	2.2	2.2	•	•	•
.025 (0.64)	1.7	1.8	1.9	2.0	2.0	2.1	2.2	2.2	2.3	2.4	2.4	•	•	•
.026 (0.66)	1.9	1.9	2.0	2.1	2.2	2.3	2.3	2.4	2.5	2.6	2.6	•	•	
.027 (0.69)	2.0	2.1	2.2	2.3	2.4	2.5	2.5	2.6	2.7	2.8	2.8	•	•	
.028 (0.71)	2.2	2.3	2.4	2.5	2.6	2.5	2.7	2.8	2.9	3.0	3.1	•	•	•
.029 (0.74)	2.3	2.4	2.5	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	•	•	
.031 (0.79)	2.6	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	•	•	•
.033 (0.84)	3.0	3.1	3.3	3.4	3.5	3.7	3.8	3.9	4.0	4.1	4.2			•
.034 (0.86)	3.2	3.3	3.5	3.6	3.8	3.9	4.0	4.2	4.3	4.4	4.5	•	•	
.035 (0.89)	3.4	3.5	3.7	3.8	4.0	4.1	4.3	4.4	4.5	4.6	4.8	•		•
.036 (0.91)	3.6	3.7	3.9	4.0	4.2	4.4	4.5	4.6	4.8	4.9	5.0	•	•	•
.037 (0.94)	3.7	3.9	4.1	4.3	4.4	4.6	4.8	4.9	5.0	5.2	5.3		•	•
.039 (0.99)	4.2	4.4	4.6	4.7	4.9	5.1	5.3	5.4	5.6	5.7	5.9	•	•	•
.047 (1.20)	6.1	6.4	6.6	6.9	7.2	7.4	7.7	7.9	8.1	8.4	8.6		•	•